



### Working at Heights – Soundstage Permanents (Horizontal Cable System)

When working outside the catwalks, in the unprotected area of the permanents known as the “ozone,” you must use fall arrest equipment. This equipment includes: a full body harness and a self-retracting lanyard (SRL) or shock absorbing lanyard. In addition, some soundstages have fixed horizontal wire rope cable fall arrest systems installed. Contact your Production Safety Representative if you have any questions about appropriate fall protection.

Prior to using any fall protection equipment, Southern CA IATSE employees are required to have passed the CSATF Safety Pass Course D – Fall Protection.

- Inspect all fall protection equipment prior to use.
- Select a horizontal line as close as possible to where you are working to avoid or limit a swing fall. These engineered lines are designed for two users per line.
- Each employee working in a controlled access zone will comply promptly with fallhazard warnings from the safety monitor.
- You may connect to the horizontal anchorage line either by:  
Connecting the SRL to the horizontal line directly with a self-locking carabiner, or Substituting a 6-foot shock-absorbing “Y” lanyard for the SRL.
- Some stages may offer the option to attach an optional transfastener (cable sleeve) directly to the cable, and then attach your SRL to the transfastener with a self-locking carabiner.)
- Attach the double-locking snap hook from the SRL to the “D” ring located on the back of your harness.
- When using an SRL, avoid quick or sudden movements in any direction to prevent loss of balance from line tension or locking. The SRL maintains normal line tension when line is being steadily extracted and retracted.
- Do not allow the SRL to go slack. Practice using the device on the catwalk. This will familiarize you with the tension and locking actions of the SRL and make you aware of the forces applied to your body by the line during movement.
- If you need to move farther than the lanyard will allow, return to the catwalk and find another horizontal line. Never try to increase the length of a lanyard by attaching it to another lanyard.
- Never detach from the lanyard until you are safely back on the catwalk.

---

Disclaimer: This website and the information contained in the Injury & Illness Prevention Program (IIPP) are intended and authorized for the use of employees of this Company only; they are not intended for, nor should they be used by, the general public or any third parties. If you have not been expressly directed to this site by the Warner Bros. Studio Operations Department of Safety & Environmental Affairs, you are not authorized to use this website and you must exit now. The IIPP is a general outline of safe work practices to be used as a guideline for our productions to provide a safe work environment for our employees. Because each particular work situation is different, these IIPP guidelines are intended to be used in conjunction with consulting the appropriate production supervisors and seeking the assistance of our Production Safety personnel. The information contained in this IIPP is not a legal interpretation of any federal, state or local regulations, laws or standards. No warranty is made about any of the contents of this website.